



## FT90 Floorslab Thickness Tester



Hd color LCD screen



UI interface Touchable design



Removable lithium battery



The probe automatically interprets the direction



### Technical advantages

- The receiving probe automatically interprets the direction and locks the center, which greatly improves the detection efficiency.
- The receiving probe and the host connect with Bluetooth, which simplifies their use and reduces the risk of failures due to frequent plugging and unplugging of signal lines.
- The instrument is equipped with a capacitive touch screen for full touch operation. Real-time display of measurement data, automatic determination of the minimum value.
- The instrument is equipped with professional software for data analysis, which transfers data between the instrument and the computer, analyzes the detection data, and generates detection reports.

### Technical parameters

Model	FT90
Measurement range	20-900mm
Maximum permissible error	20-350mm $\pm 1$ mm
	350-600mm $\pm 2$ mm
	601-900mm $\pm 3$ mm
Data storage capacity	The instrument can store data for 5,000 components locally
LCD	The instrument features a 5.0-inch full-color touch screen with a resolution of 854×480
Battery	The instrument features built-in large-capacity lithium-ion batteries
Size / Weight	[Host] Size: 200×125×50mm. Weight: 620g.
	[Transmitting probe] Size: $\Phi 90 \times 87$ (mm). Weight: 270g
	[Receiving probe] Size: $\Phi 110 \times 110$ mm. Weight: 400g